




Palm IIIx Front Button Cluster Replacement

Written By: David Haskell



INTRODUCTION

A guide to replace a damaged, lost, or broken button cluster.



TOOLS:

- [Phillips #00 Screwdriver](#) (1)



PARTS:

- [Palm IIIx Push Button](#) (1)
- [Palm IIIx Button Cluster](#) (1)

Step 1 — Battery



- Place the Palm IIIx face down on a flat surface.

Step 2



- Push down, lift up on, and remove battery cover.

Step 3



- Remove the old batteries one at a time.

Step 4 — Front Button Cluster



- Using a Phillips #00 screwdriver, remove the four screws that hold the back cover in place.

Step 5




- Hold the device on its side, positioning your hands as shown.
- Remove the back cover by pushing in with your thumbs and pulling outward with the rest of your fingers

Step 6



- Hold the screen and front cover in a vertical position, facing the screen inward, as shown.
- Position your hands so you can push the screen outward with your thumbs.
- Remove the front cover by gently pushing outward with your thumbs. Use your index fingers to pull back on the front cover.

Step 7



- Remove cluster by pulling on the rubber backing.
- Clean, repair, and/or replace as necessary.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-07-15 09:50:28 PM.